

RULE 404

Particulate Matter - Concentration

- (a) A person shall not discharge into the atmosphere from any source, particulate matter in excess of the concentration at standard conditions, shown in Table 404(a).
Where the volume discharged is between figures listed in the Table, the exact concentration permitted to be discharged shall be determined by linear interpolation.
The provisions of this subsection shall not apply to any equipment completed and put into service before July 1, 1976 in the Palo Verde and Joshua Tree areas.
Before July 1, 1983, liquid sulfur compounds shall not be included as particulate matter discharged from petroleum coke calciners.

- (b) A person shall not discharge into the atmosphere from any source, particulate matter in excess of 450 milligrams per cubic meter (0.196 grain per cubic foot) in discharged gas calculated as dry gas at standard conditions.
The provisions of this subsection shall apply only to any equipment completed and put into service before July 1, 1976 in the Palo Verde and Joshua Tree areas.

- (c) The provisions of this rule shall not apply to emissions resulting from the combustion of liquid or gaseous fuels in steam generators or gas turbines.

- (d) For the purposes of this rule, emissions shall be averaged over one complete cycle of operation or one hour, whichever is the lesser time period.

- (e) The provisions of this rule shall not apply to the use of equipment which complies with the emission limits specified in Rule 1112.1.

[SIP: Submitted as amended 2/7/86 on 6/4/86, approved for SCAQMD area only 9/2/98; Approved 9/28/81, 46 FR 47451, 40 CFR 52.220(c)(58)(ii)(B); Disapproved, prior rule 52 retained 9/8/78, 43 FR 40011, 40 CFR 52.220(c)(39)(iii)(C) and 40 CFR 52.228(b)(1)(ii)(A); Disapproved 6/14/78, 43 FR 25684, 40 CFR 52.220(c)(32)(iv)(A) and 40 CFR 52.227(b)(3)(i)]

TABLE 404(a)

Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter ⁷ Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions		Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions	
Cubic meters Per Minute	Cubic feet Per Minute	Milligrams per Cubic Meter	Grains per Cubic Foot	Cubic meters Per Minute	Cubic feet Per Minute	Milligrams per Cubic Meter	Grains per Cubic Foot
25 or less	883 or less	450	0.196	900	31780	118	0.0515
30	1059	420	.183	1000	35310	113	.0493
35	1236	397	.173	1100	38850	109	.0476
40	1413	377	.165	1200	42380	106	.0463
45	1589	361	.158	1300	45910	102	.0445
50	1766	347	.152	1400	49440	100	.0437
60	2119	324	.141	1500	52970	97	.0424
70	2472	306	.134	1750	61800	92	.0402
80	2825	291	.127	2000	70630	87	.0380
90	3178	279	.122	2250	79460	83	.0362
100	3531	267	.117	2500	88290	80	.0349
125	4414	246	.107	3000	105900	75	.0327
150	5297	230	.100	4000	141300	67	.0293
175	6180	217	.0947	5000	176600	62	.0271
200	7063	206	.0900	6000	211900	58	.0253
250	8829	190	.0830	8000	282500	52	.0227
300	10590	177	.0773	10000	353100	48	.0210
350	12360	167	.0730	15000	529700	41	.0179
400	14130	159	.0694	20000	706300	37	.0162
450	15890	152	.0664	25000	882900	34	.0148
500	17660	146	.0637	30000	1059000	32	.0140
600	21190	137	.0598	40000	1413000	28	.0122
700	24720	129	.0563	50000	1766000	26	.0114
800	28250	123	.0537	70000 or more	2472000 or more	23	.0100