

Antelope Valley Air Quality Management District

2551 West Ave H, Suite 102, Lancaster, CA 93536 Phone 661.723.8070 www.avaqmd.ca.gov

Project Signage Information

FOR ALL DUST CONTROL REQUIREMENTS REFERENCE AVAQMD RULE 403 - FUGITIVE DUST

Section 1: General Information Please email to plans@avaqmd.ca.gov

1-A Project Na	me and Location		
Project Name:			
Project Address:			
Major X-Streets:			
City:		APN #:	
Land Use Agency:	☐City of Lancaster	□City of Palmdale	☐County of Los Angeles
1-B Contacts	3		
	esses, and phone numbers of per- ntation of the Dust Control Plan ar		responsible for the preparation, erating operation and dust control
Project Owner:			
Address:			
City/State/Zip:			
Phone:	Cell Phone:	Email	:
General Contractor:			
Address:			
City/State/Zip:			
Contact Person:			
Phone:	Cell Phone:	Email	:
Dust Control Plan was	Prepared by:		
Name:			
Company Name:			
Phone:	Cell Phone:	Email	:
1-C 24 Hour	Contact		
Primary Project Contac	t:		
Company Name:			
Address:			
City/State/Zip:			
Phone:	Cell Phone:	Email	:



Antelope Valley Air Quality Management District 2551 West Ave H, Suite 102, Lancaster, CA 93536 Phone 661.723.8070 www.avagmd.ca.gov

DUST CONTROL PLAN SIGNAGE GUIDELINES (Minimum Requirements)

The purpose of this signage is to allow the public to contact the responsible party if Visible Dust Emissions or Track-out of material is observed from the site.

Sign size	48" x 96"
-----------	-----------

Sign Template

Permit # (if applicable)	4"
Site Name	4"
Project Name	4"
IF YOU SEE DUST COMING FROM THIS PROJECT CALL:	4"
Name, Phone Number (XXX) XXX-XXXX	6"
If you do not receive a response, Please call The Antelope Valley AQMD at 1-877-723-8070	3"

Signage must be located within 50 feet of each project site entrance.

No more than four signs are required per site facility.

One sign is sufficient for multiple site entrances located within 300 yards of each other.

Text height shall be at a minimum as shown on right side of sign template above.

Sign background must contrast with lettering, typically black text with white background.

Sign should be one inch AC laminated boad.

The lower edge of the sign board must be a minimum of six feet and a maximum of seven feet above grade.

The telephone number listed for the contact must be a local or a toll-free number and shall be accessible 24 hours per day.

Original signage used during site construction will satisfy the signage requirement of the Active Operation Dust Control Plan/Active Operation Dust Control Plan-Renewable Energy (if required) and can remain if contact information is current and the sign is in satisfactory condition.